




# Metal FS: File System and Data Stream Operators for FPGAs

Robert Schmid, Lukas Wenzel  
Operating Systems and Middleware Group  
30.01.2019

# Introduction: What is an FPGA?

- **Field-Programmable Gate Array**: programmable hardware circuit
- Algorithms are represented as a hardware description
- Programming:
  - VHDL (Hardware Description Language)
  - High-Level Synthesis (HLS)
- Interest in FPGAs is growing (again)
  - Energy efficiency
  - Parallel and pipelined data processing
  - 'Computing wires'
- My focus: FPGAs as part of a computer system



## Metal FS

07.02.2019  
Robert Schmid  
Lukas Wenzel  
Chart 2

# Development of Heterogenous Computing

---

- Physical limitations in general-purpose processor development
  - Energy efficiency becomes a key question
  
- FPGAs and specialized co-processors are suited for a variety of use cases
  - Google TPU (TensorFlow)
  - Microsoft HPU (HoloLens)
  - Apple T2 (MacBook, iMac Encryption)
  - Cloud FPGAs: Amazon F1, Azure ML Service
  
- Innovations in interconnects and system architecture
  - “Accelerators become first-class citizens in the system”

## **Metal FS**

07.02.2019  
Robert Schmid  
Lukas Wenzel  
Chart **3**

- 
- The diagram illustrates the components of the command `fpga-encrypt -k key.bin > encrypted_file.bin`. A red bracket above the command is labeled `'Operator'`. A red arrow points to the vertical pipe symbol `|` with the label `UNIX Pipe`. Another red arrow points to the greater-than symbol `>` with the label `Redirect Standard Output to File`.

# Metal FS

- Started as part of a File System project seminar
- Goal: Improve the accessibility of FPGA accelerators using a file system abstraction



**Foundations**

IBM POWER


CAPI + SNAP

Xilinx Vivado

## Metal FS

07.02.2019  
Robert Schmid  
Lukas Wenzel  
Chart 5

# Operators are specified in Vivado HLS



```

static snapu64_t _offset = 0;

mtl_retc_t my_metal_operator_set_offset(snapu64_t offset) {
    _offset = offset;
    return SNAP_RETC_SUCCESS;
}

void my_metal_operator(mtl_stream & in, mtl_stream & out) {
    mtl_stream_element element;
    do {
        element = in.read();
        element.data += _offset;
        out.write(element);
    } while (!element.last);
}
  
```

## Metal FS

07.02.2019  
Robert Schmid  
Lukas Wenzel  
Chart 6

# Chaining Operators

---

- What happens here?




```
$ cat encrypted_file.bin | fpga-decrypt | fpga-uppercase  
HELLO WORLD
```

- In between FPGA processing steps, data should not be copied to the CPU's main memory (slow)
- In conclusion:
  - Multiple operators must be deployed on the FPGA at once
  - Active subset and order of Operators should be configurable at runtime

# Metal FS Operator Pipelines

- Streaming Data from different types of memory
- Composition of Pipelines by using AXI Stream Switch
- C++ API



```
OperatorRegistry registry;
```

```
auto encrypt = registry.operators().at("encrypt");
encrypt->setOption("key", keyBuffer);
```

```
auto dataSource = create_data_source(inputBuffer);
auto dataSink = create_data_sink(outputBuffer);
```

```
PipelineDefinition pipeline
    ({ dataSource, encrypt, dataSink });
pipeline.run();
```


## Metal FS

07.02.2019  
Robert Schmid  
Lukas Wenzel  
Chart 8





# Metal FS: Architecture Overview



## Metal FS

07.02.2019  
 Robert Schmid  
 Lukas Wenzel  
 Chart **10**

# Metal FS Hybrid Filesystem


- Leverage the NVMe storage on the Nallatech N250S FPGA card
- One use case for Operator Pipelines
- File System Metadata is maintained in an LMDB Key-Value Store on the host
  - inodes, directory entries, free extents
- Block Mapper on the FPGA translates file offsets to physical addresses using extent lists
- All file accesses are implemented as Operator Pipelines (Read -> Write)
  - Data transformations can be transparently added (e.g. encryption)



## Metal FS

07.02.2019  
Robert Schmid  
Lukas Wenzel  
Chart 11

# Metal FS: Architecture Overview



## Metal FS

07.02.2019  
Robert Schmid  
Lukas Wenzel  
Chart **12**

# Metal FS FUSE Filesystem

---

- Users can mount Metal FS as a Linux file system
- Implemented in user space
- Example:  


```
$ cp ~/orders.tbl /metal_fs/files/
```

## **Metal FS**

07.02.2019  
Robert Schmid  
Lukas Wenzel  
Chart **13**

# Metal FS Symbolic Executables


```
$ echo "Hello World" \  
  | /metal_fs/operators/change_case \  
    | /metal_fs/operators/encrypt \  
      | /metal_fs/operators/decrypt
```



## Metal FS

07.02.2019  
Robert Schmid  
Lukas Wenzel  
Chart **14**

# Metal FS: Architecture Overview



## Metal FS

07.02.2019  
 Robert Schmid  
 Lukas Wenzel  
 Chart **15**

```
root@ubop8le:/mnt/metal_fs# t
```



# Hands-On: Set up Metal FS Simulation

---

- All terminal commands are listed in `simulation_cmd.md`
  
- Steps:
  1. Clone Metal FS: [https://github.com/osmhpi/metal\\_fs](https://github.com/osmhpi/metal_fs)
  2. Compile Metal FS Software
  3. Build Hardware Simulation Image through SNAP
  4. Start Simulation, mount Metal FS and run the `change_case` operator

## **Metal FS**

07.02.2019  
Robert Schmid  
Lukas Wenzel  
Chart **17**

# Anatomy of an Operator in Vivado HLS

- HLS translates the `mtl_stream` references into AXI Stream interfaces
- We require the `keep` and `last` signals which are optional channels in the AXI Stream protocol

```
struct mtl_stream_element {  
    ap_uint<64> data; ap_uint<8> keep; ap_uint<1> last;  
};
```

```
void my_operator(mtl_stream &in, mtl_stream &out) {  
    mtl_stream_element element;  
    do {  
        element = in.read();  
        out.write(element);  
    } while (!element.last);  
}
```

## Metal FS

07.02.2019  
Robert Schmid  
Lukas Wenzel  
Chart 18

# Programming with HLS: Arbitrary-precision integers

- HLS offers the `ap_uint` types for integers with arbitrary bit precision
- `snapu{8, 16, 32, 64}_t` are typedefs for `ap_uint<>`
- Access bit ranges of an `ap_uint` like this (similar to VHDL):  

```
snapu16_t my_integer;  
snapu8_t high_byte = my_integer(15, 8);
```
- Concatenate integers:  

```
snapu8_t high_byte = 0xFF;  
snapu8_t low_byte  = 0x0A;  
snapu16_t both_bytes = (high_byte, low_byte);
```

# Hands-On: Build a Grayscale Filter operator

---

- Goal: Implement an operator that processes a bitmap image and converts it to grayscale, except for pixels where red is the dominant color
- An operator skeleton is prepared in `metal_fs/src/metal_fpga/hw/hls/hls_action/mtl_op_image.cpp`
- Bitmap header is not aligned to an 8-byte boundary
  - The skeleton temporarily inserts a padding to make processing easier
- The Vivado HLS IDE provides debugging and analysis capabilities


## **Metal FS**

07.02.2019  
Robert Schmid  
Lukas Wenzel  
Chart **20**

# Hands-On: Build a Grayscale Filter operator

## ■ Steps

1. Implement the grayscale conversion algorithm in the `process_stream` method
  - Use the Vivado HLS IDE
2. Use the HLS Testbench to check if your algorithm works when executed as software



3. Run SNAP's `make model` to translate it into a hardware description
4. Try it out (with a scaled down image) in the simulation environment  
`/metal_fs/src/metal_fpga/hw/hls/hls_action/apples_simulation.bmp`
5. Run your operator in profiling mode, to see how well it performs  
`/operators/image -p`

## **Metal FS**

07.02.2019  
 Robert Schmid  
 Lukas Wenzel  
 Chart **21**

# Performance Counters in Metal FS

- Performance Counters for Input and Output interfaces of an Operator
  - Bytes transferred
  - Active cycles
  - Idle cycles (caused by Producer/Consumer)
  - Total cycles
- Usage

```
cat apples.bmp | /mnt/metal_fs/operators/image -p > applesbw.bmp
```

STREAM	BYTES TRANSFERRED	ACTIVE CYCLES	DATA WAIT	CONSUMER WAIT	TOTAL CYCLES	MB/s
input	6538	818	59% 568	41% 0	1389	1176.75
output	6538	818	59% 568	41% 0	1389	1176.75


# Performance Optimization in Vivado HLS

Use the HLS Pipeline pragma to reduce the 'initiation interval' of your loop iterations

`#pragma HLS PIPELINE`

- Watch out for warnings in the HLS synthesis compiler log

DataFlow Analysis View:



**Metal FS**

07.02.2019

Robert Schmid

Lukas Wenzel

Chart 23

# Hands-On: Optimize the operator performance

## ■ Steps:

1. Check if your operator is the bottleneck by using Metal FS profiling output

```
cat apples.bmp | /mnt/metal_fs/operators/image -p > applesbw.bmp
```

STREAM	BYTES TRANSFERRED	ACTIVE CYCLES	DATA WAIT	CONSUMER	WAIT	TOTAL	CYCLES	MB/s
input	6538	818	22% 502	13% 2403	64%	3729		438.32
output	6538	818	22% 2908	78% 0	0%	3729		438.32

2. Explore the Analysis View in Vivado HLS
3. Try out the HLS PIPELINE pragma

## Metal FS

07.02.2019  
Robert Schmid  
Lukas Wenzel  
Chart 24





Thank you  
for your attention!