

# Data-centric XML

## XML Schema (Part 1)

# Schema and DTD

- Disadvantages of DTD:
  - separate, non-XML syntax
  - very limited constraints on data types (just ID, IDREF, ...)
  - no support for sets (i.e. each element type must occur precisely once)
  - all elements are global (i.e. their content model applies in the entire document)
  - no support for namespaces
- Goals of XML Schema
  - description of the structure of a document
  - description of the data of a document
  - *as a document*

# References

<http://www.informatik.hu-berlin.de/~obecker/Lehre/SS2002/XML/11a-schema.xml>

- W3 Recommendations (XML Schema 1.0)
  - <http://www.w3.org/TR/xmlschema-0/> (Primer)
  - <http://www.w3.org/TR/xmlschema-1/> (Structures)
  - <http://www.w3.org/TR/xmlschema-2/> (Datatypes)
  - XML Schema 1.1: Working Draft
- Other Resources
  - <http://www.w3.org/XML/Schema>
  - <http://www.jeckle.de/xsd-de/>
  - <http://www.w3.org/2001/03/webdata/xsv>

# An Example

- Example document: catalog of a bookstore

```
<buchhandlung art="belletristik">  
  <buch>  
    <autor>...</autor>  
    <titel>...</titel>  
    <verlag>...</verlag>  
    <isbn>...</isbn>  
    <preis>...</preis>  
  </buch>  
  <buch>  
    ...  
  </buch>  
</buchhandlung>
```

## An Example (2)

- Define a schema for the document
  - Starting with boilerplate

```
<xs:schema  
    xmlns:xs="http://www.w3.org/2001/XMLSchema">  
    ...  
</xs:schema>
```

# An Example (3)

- Define the root element of the document (`buchhandlung`), which is of a complex type

```
<xs:schema  
    xmlns:xs="http://www.w3.org/2001/XMLSchema">  
    <xs:element name="buchhandlung">  
        <xs:complexType>  
            ...  
        </xs:complexType>  
    </xs:element>  
</xs:schema>
```

# An Example (4)

- A buchhandlung contains multiple buch elements, and a art attribute

```
<xs:schema
```

```
    xmlns:xs="http://www.w3.org/2001/XMLSchema">
```

```
    <xs:element name="buchhandlung">
```

```
        <xs:complexType>
```

```
            <xs:sequence>
```

```
                <xs:element name="buch"
```

```
                    maxOccurs="unbounded">
```

```
            ...
```

```
        </xs:element>
```

```
    </xs:sequence>
```

```
    <xs:attribute name="art" type="xs:string"/>
```

```
    </xs:complexType>
```

```
    </xs:element>
```

```
</xs:schema>
```

# An Example (5)

- Similarly, a buch is defined by listing its child elements

...

```
<xs:element name="buch" maxOccurs="unbounded">
  <xs:complexType>
    <xs:sequence>
      <xs:element name="autor" type="xs:string"/>
      <xs:element name="titel" type="xs:string"/>
      <xs:element name="verlag" type="xs:string"/>
      <xs:element name="isbn" type="xs:string"/>
      <xs:element name="preis" type="xs:string"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
...
```

- Complete schema follows the Matryoshka design

```
<xs:schema xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:element name="buchhandlung">
    <xs:complexType>
      <xs:sequence>
        <xs:element name="buch" maxOccurs="unbounded">
          <xs:complexType>
            <xs:sequence>
              <xs:element name="autor" type="xs:string"/>
              <xs:element name="titel" type="xs:string"/>
              <xs:element name="verlag" type="xs:string"/>
              <xs:element name="isbn" type="xs:string"/>
              <xs:element name="preis" type="xs:string"/>
            </xs:sequence>
          </xs:complexType>
        </xs:element>
      </xs:sequence>
      <xs:attribute name="art" type="xs:string"/>
    </xs:complexType>
  </xs:element>
</xs:schema>
```

# Global Element Definitions

- An element defined in a schema can be used in multiple places
  - e.g. defined through `<xs:element name="author" type="xs:string"/>` can be referred as `<xs:element ref="author"/>` inside e.g. `xs:sequence`
- Global element definitions produce a flat schema, like DTDs

# Reusable Element Types

- Structure of a type (attributes, sequence) can be given a name, and then used to define multiple elements

```
<xs:complexType name="buchlisteTyp">
  <xs:sequence>
    <xs:element ref="buch" maxOccurs="unbounded"/>
  </xs:sequence>
  <xs:attribute ref="art"/>
</xs:complexType>

<xs:element name="buchhandlung"
  type="buchlisteTyp"/>
```

# Content Models

- Like DTDs, XML Schema allows the definition of content models
- Empty content: Complex type with no content, possibly attributes

```
<xs:element name="leer">  
  <xs:complexType />  
</xs:element>
```

```
<xs:element name="leerMitAtt">  
  <xs:complexType>  
    <xs:attribute name="att" type="xs:string"/>  
  </xs:complexType>  
</xs:element>
```

# Simple Content with Attributes

- Example:

```
<buchtipp isbn="3-251-00452-2">Ein Buch, das in  
keinem Bücherschrank fehlen darf.</buchtipp>
```

- Starting with xs:simpleContent, extended with attributes

```
<xs:element name="buchtipp">  
  <xs:complexType>  
    <xs:simpleContent>  
      <xs:extension base="xs:string">  
        <xs:attribute name="isbn" type="xs:string" />  
      </xs:extension>  
    </xs:simpleContent>  
  </xs:complexType>  
</xs:element>
```

# Structured Types

- Sequences (xs:sequence): List child elements in order
- Choices (xs:choice): List alternative child elements
- Sets (xs:all): List child elements that must occur, but can occur in arbitrary order
  - Must not be part of other content models
  - Must contain only elements

# Cardinalities

- Attributes minOccurs= and maxOccurs= on xs:element (default is 1)
  - Only allowed for nested elements, not in global elements
  - Value “unbounded” means arbitrary repetition

```
<xs:element name="x" type="..."  
           minOccurs="0" maxOccurs="unbounded"/>
```

# Cardinalities Example

The DTD content model

((arbeit, essen)\*, (sport | spiel+)?, schlaf)+

translates to

```
<xs:complexType>
  <xs:sequence maxOccurs="unbounded">
    <xs:sequence minOccurs="0" maxOccurs="unbounded">
      <xs:element name="arbeit" type="..." />
      <xs:element name="essen" type="..." />
    </xs:sequence>
    <xs:choice minOccurs="0">
      <xs:element name="sport" type="..." />
      <xs:element name="spiel" type="..." maxOccurs="unbounded" />
    </xs:choice>
    <xs:element name="schlaf" type="..." />
  </xs:sequence>
</xs:complexType>
```

# Mixed Content

- Attribute mixed="true" for xs:complexType  
(#PCDATA | tier | ort)\*

```
<xs:complexType mixed="true">
  <xs:choice minOccurs="0" maxOccurs="unbounded">
    <xs:element name="tier" type="..." />
    <xs:element name="ort" type="..." />
  </xs:choice>
</xs:complexType>
```

- Also allowed for xs:sequence and xs:all

# Attributes

- xs:attribute
- Always occur after child elements
- name= specifies attribute name
- type= specifies simple type
- use="required"|"optional"
- default= specifies default value
- fixed= specifies fixed value

# XML Schema So Far

- Additions with respect to DTDs:
  - More complex cardinalities (not just +, \*, ?)
  - Set content models (xs:all)
  - Mixed Content for xs:sequence, xs:choice, xs:all